

EXTREME  
WALL PANEL

FIELD INSTALLED  
PANEL SILL PLATE

CONTINUOUS  $\frac{3}{8}$ "  
&  $\frac{1}{2}$ " PANEL  
SEALANT

$\frac{1}{2}$ " SCREWS @ 8"  
O.C. OR 2"-8d  
NAILS @ 6" O.C.  
FASTENED ON  
EACH SIDE (U.N.O.)

PANEL SCREWS W/  
WASHERS @ 12" O.C.  
W/ MINIMUM  $\frac{1}{4}$ "  
PENETRATION INTO SILL  
PLATE (U.N.O.)

OPTIONAL PANEL SCREWS

MIN.  $\frac{7}{16}$ " UNDERLAYMENT  
PERPENDICULAR TO  
PANEL SEAMS

EXTREME FLOOR PANEL

DOUBLE TREATED 2x SILL  
PLATE ATTACHED  
TOGETHER W/ 3" CONST.  
LAGS @ 24" O.C. OR 16d  
NAILS @ 12" O.C. IN 2  
ROWS STAGGERED (U.N.O.)  
W/ PANEL SEALANT  
BETWEEN 2x's

SILL SEALER

CONCRETE OR  
MASONRY FOUNDATION

ANCHOR BOLTS  
PLACED PER  
CODE

SECTION  
NOT TO SCALE

DETAIL TITLE : PANEL FLOOR TO FOUNDATION

DETAIL NO. : EP-208

PAGE NO. : 2 - 8

UPDATED : MARCH 2017

**Extreme Panel**

TECHNOLOGIES, INC.

STRUCTURAL INSULATED PANELS