

1 1/2" SCREWS @ 8" O.C. OR 2"-8d NAILS @ 6" O.C. ALONG RAFTER TAIL (U.N.O.)

PANEL SCREWS W/ WASHERS @ 12" O.C. W/ MINIMUM 1 1/4" PENETRATION INTO TOP PLATE MATERIAL

1 1/2" SCREWS OR 2"-8d NAILS @ 12" O.C. STAGGERED IN 5/8" PLYWOOD SPLINE

7/16" OSB ROOF SHEATHING

2x6 RAFTER TAIL CUT TO SPECIFIED OVERHANG LENGTH

2x RAFTER TAIL SUPPORT CUT TO FIT SPACE BETWEEN RAFTER TAIL AND BOTTOM SKIN OF ROOF PANEL ATTACHED W/ 3" CONST. LAGS OR 1 6d NAILS (USED W/ OVERHANGS 2'-0" AND UNDER)

NOTE:
OVERHANGS BETWEEN 2'-0" - 3'-0" MUST HAVE ADDITIONAL SUPPORT W/ 2x LOOKOUTS. OVER 3'-0" REQUIRES HEADER SUPPORT.

SECTION
NOT TO SCALE

NOTE: MAXIMUM 42# LIVE LOAD

EXTREME ROOF PANEL

USE 2-PART EXPANDABLE FOAM TO SEAL GAPS AROUND TAIL POCKET MATERIAL AFTER INSTALLATION

FACTORY REMOVED EPS FOAM VOID TO ALLOW INSERTION OF RAFTER TAIL

6" SIP TAPE ON (WINTER) WARM SIDE OF PANEL

2x BEVELED TOP PLATE (SEE DETAIL EP-402)

EXTREME WALL PANEL

NOTE:
2x4 RAFTER TAILS ARE USED W/ 8 1/4" ROOF PANELS

DETAIL TITLE : RAFTER TAIL EAVE

DETAIL NO. : EP-418

PAGE NO. : 4 - 18

UPDATED : MARCH 2017

Extreme Panel

TECHNOLOGIES, INC.

STRUCTURAL INSULATED PANELS