

Utilized panels for the floor, walls, and roof of this house






The attic was utilized for HVAC and storage purposes.



ஸ்

The attic space, typically hot, is now being used for HVAC and storage purposes.





Vaulted ceilings.





Flat ceilings were installed to create a conditioned attic space.



How do the numbers work?

- SIP house requires 80% less framing labor compared to a stick-framed house.
- SIP construction generates zero on-site waste.
- SIP-framed house achieves a HERS score of 54, while a stick-framed house scores 80+.
- SIP framing allows for windows and doors to be installed in just 2 days, while conventional stick framing takes over 30 days.
- SIP construction can potentially save \$103.80 per month on energy costs with a 30-year mortgage, assuming energy costs remain constant, providing extra funds for other bills.





Project: Goldwire

SIPs Savings/Value vs. Conventional Framing The following details outline the potential cost savings using SIPs

Total SIPs Saving + Value Over Conventional Framing:	\$ 55,662
Details: Total Cost Comparison	\$ -16,438
Total Costs with Traditional Framing Total Cost Using SIPs Total Cost Savings (Framing Cost - SIPS Cost)	\$ 95,120 \$ 111,558 \$ -16,438



Details: SIPs Improved User Experience	\$ 57,900
Stronger/More Dimensionally Accurate Enclosure Greater Resilience to Fire, Wind, Impact, Pests	\$0 \$0
High Appraisals to Base Price	\$ 20,520
Reduced Home Insurance Annual Insurance Cost	\$0
Additional Square Footage with Thinner Walls	\$0
Sq. Ft. of SIP Attic Traded Off for Basement	\$0
Additional Conditioned Space with SIP Attic	\$0
45L Tax Credit	\$0
Utility Rebate	\$0
30-year Energy Savings	\$ 37,380
Total Added Value	\$ 57,900

Improved Building

Details: Value of Construction Time Saved vs. Framing

Total Number of Construction Days	Conventional Framing	61.5
	Using SIPs	26.0
Value of Saved Days	\$ 14,200	

